## TECH BRIEF

# 75

### **NEW:** RONDO TOP HAT CLEATS



Rondo is proud to release its new range of specialised Fixing Cleats to suit our standard 50 & 75mm wide Top Hats. >>




### RONDO TOP HAT CLEATS

Rondo Top Hat Cleats enable fixing to structural steel or masonry/concrete substrates as well as to steel stud framing and allow adjustment to plumb and level.


They are available in two depths of 35 and 55mm and are manufactured from 1.9 bmt G2 Z275 Bluescope steel.




The images below show the basic fixing details for both the cleats and the attaching of the top hat profiles.



CLEAT TO STEELWORK



CLEAT TO CONCRETE



VERTICAL METHOD TO STEEL STUD FRAMING

#### **SPECIFICATIONS**

PART NUMBER	DESCRIPTION	PACK QUANTITY
550	50 x 55 x 1.9 bmt	50
535	50 x 35 x 1.9 bmt	50
750	75 x 55 x 1.9 bmt	50
735	75 x 35 x 1.9 bmt	50

Full fixing details for the Rondo Top Hat Cleats are to be found in the new Rondo Design Manual due for release in September 2013, or from our website. For more information contact your local Rondo Sales Office on 1300 – 36 – RONDO (1300 – 36 – 7663).

